



**BASSWORX**

industrial revolution

enclosures

# Enclosure Specifications (North America)

MODEL	DIMENSION (IN)			PROFILE	VOLUME (CU FT)	TUNING (HZ)	MDF BODY	MDF BAFFLE	MOUNTING DEPTH	MOUNTING DIAMETER
	LENGTH	WIDTH	HEIGHT							
<b>COMPACT - SEALED</b>										
CS8B	10.625"	9.875"	9.25"	wedge	0.35	n/a	5/8"	5/8"	7.75"	7"
CS10B	13"	10.625"	11.5"	wedge	0.6	n/a	5/8"	5/8"	8"	9.375"
CS12B	15.5"	12"	13.75"	wedge	1	n/a	5/8"	5/8"	8.75"	11.125"
CS15B	22.5"	11"	15.75"	wedge	1.5	n/a	5/8"	5/8"	7.5"	14"
CS210B	24"	11"	11.5"	wedge	1.2	n/a	5/8"	5/8"	8"	9.375"
CS212B	29.125"	12.25"	13.75"	wedge	2	n/a	5/8"	5/8"	9"	11.125"
CS215B	33.875"	12.75"	15.75"	wedge	2.8	n/a	5/8"	5/8"	9.25"	14"
<b>COMPACT - PORTED</b>										
CP10B	19.75"	12.5"	11.5"	wedge	1.1	50	5/8"	5/8"	9.75"	9.375"
CP12B	23.5"	11.5"	13.75"	wedge	1.4	48	5/8"	5/8"	8.5"	11.125"
CP15B	26.75"	13.75"	15.75"	wedge	2.25	46	5/8"	5/8"	10.25"	14"
CP210B	27.75"	14.75"	11.5"	wedge	2	50	5/8"	5/8"	12.25"	9.375"
CP212B	33"	14"	13.75"	wedge	2.6	48	5/8"	5/8"	10.75"	11.125"
<b>REFERENCE - SEALED</b>										
HSR10	17.375"	9.25"	12.875"	wedge	0.7	n/a	3/4"	3/4" + 1/4"	6.5"	9.375"
HSR12	19.5"	11.5"	14.875"	wedge	1.2	n/a	3/4"	3/4" + 1/4"	8.5"	11.125"
HSR210	27"	10.5"	13.75"	wedge	1.4	n/a	3/4"	3/4" + 1/4"	7.5"	9.375"
HSR212	31.375"	12.5"	15.75"	wedge	2.4	n/a	3/4"	3/4" + 1/4"	9.5"	11.125"
<b>REFERENCE - PORTED</b>										
HPR10	17.25"	15"	12.875"	wedge	1.25	46	3/4"	3/4" + 1/4"	11.75"	9.375"
HPR12	19.5"	16.25"	14.875"	wedge	1.65	42	3/4"	3/4" + 1/4"	12.5"	11.125"
HPR210	31.5"	13.75"	13.25"	wedge	2.2	46	3/4"	3/4" + 1/4"	10.5"	9.375"
HPR212	33"	15.625"	15.75"	wedge	3	42	3/4"	3/4" + 1/4"	12.25"	11.125"
<b>INVERTED - PORTED</b>										
SLR210	29"	17.625"	14"	trapezoid	2.2	46	3/4"	3/4" + 1/4"	8"	9.375"
SLR212	33"	20"	14"	trapezoid	2.8	42	3/4"	3/4" + 1/4"	8"	11.125"
<b>GLOSS - PORTED</b>										
GPH10BK	22"	14.375"	13.5"	wedge	1.4	40	3/4"	3/4"	11.75"	9.375"
GPH12BK	22.5"	16"	15.5"	wedge	1.9	38	3/4"	3/4"	13.25"	11.125"
GPH210BK	31.5"	16.25"	13.5"	wedge	2.4	40	3/4"	3/4"	11.5"	9.375"
GPH212BK	33.5"	18"	15.5"	wedge	2.8	38	3/4"	3/4"	15"	11.125"
GPH212S	33.5"	18"	15.5"	wedge	2.8	38	3/4"	3/4"	15"	11.125"
GPH212R	33.5"	18"	15.5"	wedge	2.8	38	3/4"	3/4"	15"	11.125"
GPH212BL	33.5"	18"	15.5"	wedge	2.8	38	3/4"	3/4"	15"	11.125"
<b>EXTREME GLOSS - EXTREME SLOT PORTED</b>										
GPX12HD	21.75"	16	17.5"	square	1.8	36	1"	1"	10.75"	11.375"
GPX212HD	34"	16.625"	16.5"	square	3.2	36	1"	1"	10.75"	11.375"
<b>SHALLOW WOOFER - SEALED</b>										
PSW2541	23"	6"	14"	wedge	0.6	n/a	5/8"	5/8"	3"	9.375"
PSW3041	26"	6.5"	16"	wedge	0.8	n/a	5/8"	5/8"	3.5"	11"
<b>TRUCK</b>										
TP10B	21"	7.75"	13.5"	wedge	0.75	45	5/8"	5/8"	5.75"	9.375"
TP12B	28"	8.5"	14.75"	wedge	1.25	45	5/8"	5/8"	6.25"	11.125"
TP210B	40"	7.75"	13.5"	wedge	1.5	45	5/8"	5/8"	5.75"	9.375"
TP212B	43.625"	8.5"	14.75"	wedge	2	45	5/8"	5/8"	6.25"	11.125"
<b>SPECIALTY TRUCK</b>										
SIERRAC210	52"	12.5"	9.75"	irregular	1.6	n/a	5/8"	3/4"	5.5"	9.375"
YUKON210	40"	13"	17"	irregular	2.7	n/a	5/8"	3/4"	13"	9.375"
F150SC210A	43"	8"	13"	irregular	2.1	n/a	5/8"	3/4"	6.5"	9.375"
SIERRAX210	50"	14.5"	9.75"	irregular	1.5	n/a	5/8"	3/4"	5.5"	9.375"
F150X210B	50"	11.125"	7.75"	irregular	1.3	n/a	5/8"	3/4"	5.25"	9.375"
RAMQ210	57"	13.375"	7.875"	irregular	1.3	n/a	5/8"	3/4"	6.5"	9.375"
F150X210A	50"	14"	7.25"	irregular	1.3	n/a	5/8"	3/4"	5.5"	9.375"
CHEVY10S10	15"	7"	18"	irregular	0.55	n/a	5/8"	3/4"	5.25"	9.375"
CHEVY10X	23.625"	13"	7.5"	irregular	0.55	n/a	5/8"	3/4"	5.5"	9.375"
CHEVY210X	61.5"	8.375"	10.25"	irregular	1.2	n/a	5/8"	3/4"	6"	9.375"
DODGET210C	49"	17.5"	10.625"	irregular	1.3	n/a	5/8"	3/4"	6"	9.375"
FORD1508	33.25"	11.5"	5"	irregular	0.55	n/a	5/8"	3/4"	4.375"	7.125"
<b>FULL-RANGE</b>										
6911CX2	11.125"	8.5"	5.625"	irregular	0.15	n/a	1/2"	1/2"	5.75" x 8.75"	5"



# Enclosure Specifications (International)

MODEL	DIMENSION (MM)			PROFILE	VOLUME (LITERS)	TUNING (HZ)	MDF BODY	MDF BAFFLE	MOUNTING DEPTH	MOUNTING DIAMETER
	LENGTH	WIDTH	HEIGHT							
<b>COMPACT - SEALED</b>										
CS8B	270	250	235	wedge	9.9	n/a	15mm	15mm	195mm	178mm
CS10B	330	270	294	wedge	18.4	n/a	15mm	15mm	205mm	238mm
CS12B	395	304	350	wedge	28.3	n/a	15mm	15mm	225mm	283mm
CS15B	570	279	400	wedge	42.5	n/a	15mm	15mm	190mm	356mm
CS210B	610	278	294	wedge	36.8	n/a	15mm	15mm	205mm	238mm
CS212B	740	310	350	wedge	56.6	n/a	15mm	15mm	230mm	283mm
CS215B	860	324	400	wedge	79.2	n/a	15mm	15mm	235mm	356mm
<b>COMPACT - PORTED</b>										
CP10B	430	268	235	wedge	17.0	50	15mm	15mm	215mm	178mm
CP12B	500	315	294	wedge	31.0	50	15mm	15mm	205mm	238mm
CP15B	595	293	350	wedge	40.0	48	15mm	15mm	215mm	283mm
CP210B	680	348	400	wedge	64	46	15mm	15mm	260mm	356mm
CP212B	730	375	294	wedge	56.6	50	15mm	15mm	310mm	238mm
CP215B	837	354	350	wedge	73.5	48	15mm	15mm	275mm	283mm
<b>REFERENCE - SEALED</b>										
HSR10	440	236	327	wedge	19.8	n/a	18mm	18mm + 6mm	165mm	238mm
HSR12	494	290	377	wedge	34.0	n/a	18mm	18mm + 6mm	215mm	283mm
HSR210	686	265	350	wedge	39.6	n/a	18mm	18mm + 6mm	195mm	238mm
HSR212	796	320	400	wedge	68	n/a	18mm	18mm + 6mm	240mm	283mm
<b>REFERENCE - PORTED</b>										
HPR10	438	381	327	wedge	34.0	46	18mm	18mm + 6mm	300mm	238mm
HPR12	495	413	378	wedge	46.7	42	18mm	18mm + 6mm	320mm	283mm
HPR210	800	349	337	wedge	62.3	46	18mm	18mm + 6mm	270mm	238mm
HPR212	838	397	400	wedge	84.9	42	18mm	18mm + 6mm	310mm	283mm
<b>INVERTED - PORTED</b>										
SLR210	737	448	356	trapezoid	62.3	46	18mm	18mm + 6mm	215mm	238mm
SLR212	838	508	356	trapezoid	79.2	42	18mm	18mm + 6mm	215mm	283mm
<b>GLOSS - PORTED</b>										
GPH10BK	559	365	343	wedge	39.6	40	18mm	18mm	300mm	238mm
GPH12BK	572	406	394	wedge	53.8	38	18mm	18mm	335mm	283mm
GPH210BK	800	413	343	wedge	67.9	40	18mm	18mm	290mm	238mm
GPH212BK	851	457	394	wedge	79.2	38	18mm	18mm	380mm	283mm
GPH212S	851	457	394	wedge	79.2	38	18mm	18mm	380mm	283mm
GPH212R	851	457	394	wedge	79.2	38	18mm	18mm	380mm	283mm
GPH212BL	851	457	394	wedge	79.2	38	18mm	18mm	380mm	283mm
<b>EXTREME GLOSS - PORTED</b>										
GPX12HD	552	406	445	square	50.9	36	25mm	25mm	270mm	289mm
GPX212HD	864	422	419	square	90.6	36	25mm	25mm	270mm	289mm
<b>SHALLOW WOOFER - SEALED</b>										
PSW2541	584	152	356	wedge	17.0	n/a	15mm	15mm	75mm	238mm
PSW3041	660	165	406	wedge	22.6	n/a	15mm	15mm	90mm	279mm
<b>TRUCK</b>										
TP10B	533	197	343	wedge	21.2	45	15mm	15mm	175mm	238mm
TP12B	711	216	375	wedge	35.4	45	15mm	15mm	195mm	283mm
TP210B	1016	197	343	wedge	42.5	45	15mm	15mm	175mm	238mm
TP212B	1108	216	375	wedge	56.6	45	15mm	15mm	195mm	283mm
<b>SPECIALTY TRUCK</b>										
SIERRAC210	1321	318	248	irregular	45.3	n/a	15mm	15mm	140mm	238mm
YUKON210	1016	330	432	irregular	76.4	n/a	15mm	15mm	330mm	238mm
F150SC210A	1092	203	330	irregular	59.4	n/a	15mm	15mm	165mm	238mm
SIERRAX210	1270	368	248	irregular	42.5	n/a	15mm	15mm	140mm	238mm
F150X210B	1270	283	197	irregular	36.8	n/a	15mm	15mm	135mm	238mm
RAMQ210	1448	340	200	irregular	36.8	n/a	15mm	15mm	165mm	238mm
F150X210A	1270	356	184	irregular	36.8	n/a	15mm	15mm	135mm	238mm
CHEVY10S10	381	178	457	irregular	15.6	n/a	15mm	15mm	135mm	238mm
CHEVY10X	600	330	191	irregular	15.6	n/a	15mm	15mm	135mm	238mm
CHEVY210X	1562	213	260	irregular	34.0	n/a	15mm	15mm	150mm	238mm
DODGET210C	1245	445	270	irregular	36.8	n/a	15mm	15mm	150mm	238mm
FORD1508	845	292	127	irregular	15.6	n/a	15mm	15mm	110mm	181mm
<b>FULL-RANGE</b>										
6911CX2	283	216	143	irregular	4.2	n/a	12mm	12mm	145mm	127mm